



# Technical Data

Document Reference  
Data Sheet

## TELDOR EQV

### RAMCRO

For standard applications, flame retardant, UV resistant

Multi-Core, HT 105°-Insulation, Collective Screen, PVC Oil Res-Sheath

SAS0507HBACX-T-UL

#### Application

Power & Control Cable

#### Construction

		Unit	Nominal Value
Formation	5 Cores		
Section	22 AWG		
Conductor	tinned copper wire, 7 strand		
Insulation	Hi Temperature polyvinyl chloride - PVC HT 105°C	mm	1,3
Colour Code	See the table		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	polyvinyl chloride - PVC Oil Resistant - Grey RAL 7001	mm	5,5
Cable Printing	RAMCRO Italy Type TC - 5 x 22AWG CU CL2/PVC/CAM/PVC 600V MIL UL 1581 105°C month+year + BATCH + METER MARKING		

#### Technical Data & Standard References

Fire Propagation:	
- Test on single cable	IEC 60332-1
- Test on bunched cables	IEC 60332-3
Limiting Oxygen Index (LOI)	ASTM D 2863 (min 30%)
Flammability temperature (FT)	
Amount of halogen acid gas	IEC 60754-1 (max 1,3%)
Sunlight resistance	UL 1581 section 1200
Type of Cable:	Power & Control Cable
Low Voltage Directive	2006/95/EC

Teldor Color Code (Up to 12 Conductors)			
N°	Color Code	N°	Color Code
1	Black	10	Grey
2	White	11	Pink
3	Red	12	Light Brown
4	Green	13	Black + White Ring
5	Brown	14	White + Black Ring
6	Blue	15	Red + Black Ring
7	Orange	16	Green + Black Ring
8	Yellow	17	Brown + Black Ring
9	Purple	18	Blue + Black Ring

#### Electrical & Mechanical Data

Conductor Cross-section	Nom.	22 AWG	Temperature Range:		
DC Resistance per core at 20° C	max	Ω/km	During Operation		° C
Insulation Resistance at 20° C	min	MΩ*km	During Installation	° C	-5° C up to +50°C
Mutual Capacitance	max	nF/km			
Inductance	max	mH/km	Min. Bending Radius	mm	6 x cable diameter
Test Voltage - Core/Core	V	2000	Weight Approx	kg/km	46,85
Test Voltage - Core/Screen	V	2000			
L/R Ratio	max	μH/Ω			
Operating Voltage	V	600			

Issued by: Davide

Prepared by RAMCRO Tech

Creator: LDG

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

Transfer to third parties only under authorization by Ramcro S.p.A.

Printing errors excepted. Subject to alterations.



Date of issue:

25/08/2015 00:00

Form I